

SCHEDULE 1 OF PART 4 – TRADE WASTE AND WASTE WATER

APPENDIX A: APPLICATION FOR TRADE WASTE DISCHARGE

HAURAKI DISTRICT COUNCIL APPLICATION FOR TRADE WASTE DISCHARGE PLEASE PRINT CLEARLY	
---	---

TRADE NAME & STREET ADDRESS OF TRADE PREMISES

.....

Phone:

After Hours Contact:

Phone:

Fax:

E-mail:

POSTAL ADDRESS OF CUSTOMER FOR CHARGING

Name:

Address:

.....

OWNER OF PREMISES (if different from above)

Name:

Address:

.....

ADDRESS FOR SERVICE FOR FUTHER ENQUIRIES CONCERNING THIS APPLICATION

Name:

Address:

.....

Phone:

Fax:

E-Mail:

LEGAL DESCRIPTION OF THE PROPERTY

.....

.....

.....

DESCRIPTION OF MAIN TRADE ACTIVITY

.....

.....

.....

THIS APPLICATION RELATES TO:

Proposed new discharge

An existing discharge for which no consent exists. Current point or place discharge

.....

Renewal of a consent

Variation to an existing consent; Nature of variation:

.....

.....

TERM OF CONSENT SOUGHT

From:

For a period of:

1 year 2 year 5 year

other (specify)

ARE THE PREMISES ALREADY CONNECTED TO PUBLIC SEWER?

Yes No

CONNECTIONS REQUIRED

Size: No:

Size: No:

Note – minimum size 100mm

SIGNATURE BLOCK

.....
(Full name)

.....
(Position)

1. I am duly authorised to make this application.
2. I believe that all the information contained in this application is true and correct.

Signature:

E-mail:

FOR OFFICE USE ONLY

APPLICATION NUMBER
.....

APPLICATION RECEIVED AND CHECKED BY
Inspector/Clerk: Date:

Permitted Controlled Conditional

PROPERTY LINK IDENTIFICATION NUMBER
.....

BUILDING CONSENT NUMBER
.....

TRADE WASTE CONSENT
Approved By:

No: Date:

APPLICATION FEE

	\$
GST	\$
TOTAL	\$

DIAGRAM FOR CONNECTION LOCATION (show distances from boundaries, kerbs, buildings) (Submit separate plan if necessary)

SCHEDULE 1 OF PART 4 – TRADE WASTE AND WASTE WATER

APPENDIX B: DESCRIPTION OF TRADE WASTE AND PREMISES

DESCRIPTION OF TRADE WASTE AND PREMISE – PLEASE PRINT CLEARLY

<p>1.1 Trade name and street address of trade waste premises Phone: Fax: E-mail:</p> <p>1.2 Name and Address of owner/occupier Name: Address: Phone: Fax: E-mail:</p> <p>1.3 Contact for enquiries (if different from above) Name: Address: Phone: Fax: E-mail:</p> <p>1.4 Total volume of wastes:</p> <table style="width: 100%; border: none;"> <tr> <td style="padding-left: 20px;">Average daily volume</td> <td style="text-align: right;">.....m³</td> </tr> <tr> <td style="padding-left: 20px;">Maximum volume in any 8 hr period</td> <td style="text-align: right;">.....m³</td> </tr> <tr> <td style="padding-left: 20px;">Maximum daily volume</td> <td style="text-align: right;">.....m³</td> </tr> <tr> <td style="padding-left: 20px;">Seasonal fluctuation (range)</td> <td style="text-align: right;">.....</td> </tr> </table> <p>1.5 General characteristics of wastes: TYPICAL RANGE</p> <table style="width: 100%; border: none;"> <tr> <td style="padding-left: 20px;">Temperature (°C)</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">BOD₅ (mg/L)</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">COD (mg/L)</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">Suspended solids (mg/L)</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">pH</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">Fat, oil and grease (g/m³)</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">TKN</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">Total Nitrogen (g/m³)</td> <td style="text-align: right;">.....</td> </tr> <tr> <td style="padding-left: 20px;">Total Phosphorus (g/m³)</td> <td style="text-align: right;">.....</td> </tr> </table> <p>1.6 The source of water used on the premises is: (a) from Councilm³/ working day (b) from other sources (<i>state source</i>) m³/ working day </p> <p>1.7 The waste do/do not, contain condensing water or storm water and the layout of drains on the premises is/ is not, such as to reasonably exclude the possibility of such becoming mixed with trade waste.</p> <p>1.8 It is/ is not proposed that domestic wastewater and trade waste should be discharged at the same point of discharge.</p> <p>1.9 The proposed method for flow measurement is:</p> <p><input type="checkbox"/> A permanent installation of suitable flow measuring equipment.</p> <p><input type="checkbox"/> Based on water usage as measure by meter</p> <p><input type="checkbox"/> Other (<i>specify</i>)</p>	Average daily volumem ³	Maximum volume in any 8 hr periodm ³	Maximum daily volumem ³	Seasonal fluctuation (range)	Temperature (°C)	BOD ₅ (mg/L)	COD (mg/L)	Suspended solids (mg/L)	pH	Fat, oil and grease (g/m ³)	TKN	Total Nitrogen (g/m ³)	Total Phosphorus (g/m ³)	<p>1.10 List any substances contained in Schedule 1A or 1B of the Part 4 (Trade Waste and Wastewater) of the Consolidated Bylaw 2007 which are stored, used, or generated on the premises. Described mitigation measures employed to prevent accidental spillages of these substances from entering the public sewer or storm water system. </p> <p>1.11 Site plans of the premises are attached which clearly show the location of the following as appropriate:</p> <table style="width: 100%; border: none;"> <tr> <td><input type="checkbox"/> Process areas</td> <td><input type="checkbox"/> flow measuring devices</td> </tr> <tr> <td><input type="checkbox"/> Trade waste drains</td> <td><input type="checkbox"/> emergency spill</td> </tr> <tr> <td><input type="checkbox"/> Stormwater drains</td> <td><input type="checkbox"/> emergency spill</td> </tr> <tr> <td colspan="2"><input type="checkbox"/> Other (<i>specify</i>)</td> </tr> </table> <p>Main trade waste pre-treatment systems</p> <table style="width: 100%; border: none;"> <tr> <td><input type="checkbox"/> Screens</td> <td><input type="checkbox"/> pH control</td> </tr> <tr> <td><input type="checkbox"/> flow balance</td> <td><input type="checkbox"/> grease traps</td> </tr> <tr> <td><input type="checkbox"/> chemical treatment</td> <td><input type="checkbox"/> biological treatment</td> </tr> </table> <p>1.12 Detailed drawings and descriptions for the following are attached as appropriate:</p> <p><input type="checkbox"/> Pre-treatment systems</p> <p><input type="checkbox"/> Flow measuring devices</p> <p><input type="checkbox"/> Emergency spill containment</p> <p><input type="checkbox"/> Sampling points</p> <p><input type="checkbox"/> Method of flow meter calibration</p> <p>1.13 An independent waste audit of the premises has/ has not been carried out by: </p> <p>1.14 A discharge Management Plan is/ is not attached. </p> <p>1.15 The health and safety requirements and security arrangements for wastewater authority staff entering the premises are as follows: (<i>specify</i>) </p>	<input type="checkbox"/> Process areas	<input type="checkbox"/> flow measuring devices	<input type="checkbox"/> Trade waste drains	<input type="checkbox"/> emergency spill	<input type="checkbox"/> Stormwater drains	<input type="checkbox"/> emergency spill	<input type="checkbox"/> Other (<i>specify</i>)		<input type="checkbox"/> Screens	<input type="checkbox"/> pH control	<input type="checkbox"/> flow balance	<input type="checkbox"/> grease traps	<input type="checkbox"/> chemical treatment	<input type="checkbox"/> biological treatment
Average daily volumem ³																																								
Maximum volume in any 8 hr periodm ³																																								
Maximum daily volumem ³																																								
Seasonal fluctuation (range)																																								
Temperature (°C)																																								
BOD ₅ (mg/L)																																								
COD (mg/L)																																								
Suspended solids (mg/L)																																								
pH																																								
Fat, oil and grease (g/m ³)																																								
TKN																																								
Total Nitrogen (g/m ³)																																								
Total Phosphorus (g/m ³)																																								
<input type="checkbox"/> Process areas	<input type="checkbox"/> flow measuring devices																																								
<input type="checkbox"/> Trade waste drains	<input type="checkbox"/> emergency spill																																								
<input type="checkbox"/> Stormwater drains	<input type="checkbox"/> emergency spill																																								
<input type="checkbox"/> Other (<i>specify</i>)																																									
<input type="checkbox"/> Screens	<input type="checkbox"/> pH control																																								
<input type="checkbox"/> flow balance	<input type="checkbox"/> grease traps																																								
<input type="checkbox"/> chemical treatment	<input type="checkbox"/> biological treatment																																								

SCHEDULE 1 OF PART 4 – TRADE WASTE AND WASTE WATER

APPENDIX C: APPLICATION FOR TEMPORARY DISCHARGE

HAURAKI DISTRICT COUNCIL APPLICATION FOR TRADE WASTE DISCHARGE



PLEASE PRINT CLEARLY

APPLICANT

Phone:

After Hours Contact:

Phone:

Fax:

Applicant responsible for liquid waste

Transportation

Generation

GENERATOR/TRANSPORTER OF LIQUID WASTE
(delete applicant's responsibility)

Name:

Company:

Address:

APPLICATION SOUGHT FOR

One discharge

A number of discharges of the same kind of liquid

PROPOSED POINT OF DISPOSAL

.....

.....

If from premises to public sewer, which is existing trade waste consent number?

PROPOSED TIMING OF DISPOSAL

Time:

Date:

LIQUID WASTE

Quantity:..... m³

Source: :

.....

.....

Process in which waste is produced:

.....

.....

.....

General characteristics:

BOD₅: (g/m³)

COD: (g/m³)

Suspended solids: (g/m³)

pH:

Fat, oil and grease: (g/m³)

TKN: (g/m³)

Total N: (g/m³)

Total P: (g/m³)

List any characteristics which are likely to be greater than 50% of concentrations stipulated in Schedule 1A of the Trade Waste Bylaw

.....

.....

ANALYSIS

Appended

Not required

DECLARATION

We hereby certify that the above liquid waste is accurately described

Applicant:

FOR OFFICE USE ONLY

APPLICATION NUMBER

TEMPORARY DISCHARGE FEE

.....	\$
GST	\$
TOTAL

APPLICATION
 Received
 by:.....Date:.....

Discharge: Approved
 Not approved

By
 Date:

Cashier Receipt:

TEMPORARY DISCHARGE

If approved:
 Where discharged:.....
 Time and date:.....

If not approved:
 Where referred to:.....

File No.

SCHEDULE 1 OF PART 4 – TRADE WASTE AND WASTE WATER

APPENDIX D: CONSENT FORM

HAURAKI DISTRICT COUNCIL
CONSENT TO DISCHARGE TRADE WASTE
TO THE PUBLIC SEWER

Pursuant to Part 4 – (Waste and Water) of the Hauraki District Council Bylaw 2007



To:.....
 (Consent holder trade name)

Address:.....
 (Street address of trade premises)

Phone:..... Fax:.....

Name:.....
 (Contact name)

Address:.....
 (Address for charging and service of documents)

.....
 (Trade activity)

In response to, and in terms of, the information declared in your application of.....(date) to discharge Trade Waste from the above premises, the consent of the Council is hereby given for the term and subject to the conditions set out below:

6. That this consent is subject to the specific conditions set out in Schedule 1A which is attached.

For and on behalf of the Hauraki District Council

1. That this consent relates to a proposed new discharge/an existing non-consented discharge/renewal of a consent/variation to an existing consent.
2. That this is a permitted conditional consent.
3. That the provisions of Part 4 (Trade Waste and Wastewater) of the Hauraki District Council Consolidated Bylaw, 2007 are complied with at all times.
4. That this consent is valid for a period of...years and will expire on.....
5. That the Trade Waste discharged under this consent shall consist only of wastes from the following processes:

Authorised Officer:
 Name:.....
 Signature:.....
 Date:.....

.....

FOR OFFICE USE ONLY

Consent No:.....

Application No:.....

File No:.....

SCHEDULE 1A OF PART 4 – TRADE WASTE AND WASTE WATER

PERMITTED DISCHARGE CHARACTERISTICS

1A.1 Introduction

1A.1.1

The nature and levels of the characteristics of any trade waste discharged to the Council's system shall comply at all times with the following requirements, except where the nature and levels of such characteristics are varied by the Council as part of an approval to discharge a trade waste.

1A.1.2

The Council shall take into consideration the combined effects of trade waste discharges and may make any modifications to the following acceptable characteristics for individual discharges the Council believes are appropriate.

1A.1.3

An additional column in tables 1A.1, 1A.2 and 1A.3 for mass limits may be added as required.

1A.1.4

The nature and levels of any Characteristic may be varied to meet any new resource consents or other legal requirements imposed on the Council, refer to clause 2.5.15 of Part 4 (Waste and Water) of the Hauraki District Bylaw, 2007.

1A.2 Physical characteristics

1A.2.1 *Flow*

- (a) The 24 hour flow volume shall be less than 5 m³.
- (b) The maximum instantaneous flow rate shall be less than 2.0 L/s.

1A.2.2 *Temperature*

The temperature shall not exceed 40 °C.

1A.2.3 *Solids*

- (a) Non-faecal gross solids shall have a maximum dimension which shall not exceed 15 mm.
- (b) The suspended solids content of any trade waste shall have a maximum concentration which shall not exceed 2000 g/m³. For significant industry this may be reduced to 600 g/m³.
- (c) The settleable solids content of any trade waste shall not exceed 50 (g/m³).
- (d) The total dissolved solids concentration in any trade waste shall be subject to the approval of the Council having regard to the volume of the waste to be discharged, and the suitability of the drainage system and the treatment plant to accept such waste.
- (e) Fibrous, woven, or sheet film or any other materials which may adversely interfere with the free flow of sewage in the drainage system or treatment plant shall not be present.

1A.2.4 *Oil and grease*

- (a) There shall be no free or floating layer.
- (b) A trade waste with mineral oil, fat or grease unavoidably emulsified, which in the opinion of the Council is not biodegradable shall not exceed 200 g/m³ as petroleum ether extractable matter when

the emulsion is stable at a temperature of 15 °C and when the emulsion is in contact with and diluted by a factor of 10 by raw sewage, throughout the range of pH 6.0 to pH 10.0.

- (c) A trade waste with oil, fat or grease unavoidably emulsified, which in the opinion of the Council is biodegradable shall not exceed 500 g/m³ when the emulsion is stable at a temperature of 15 °C and when the emulsion is in contact with and diluted by a factor of 10 by raw sewage throughout the range of pH 4.5 to pH 10.0.
- (d) Emulsified oil, fat or grease shall not exceed 100 g/m³ as petroleum ether extractable matter when the emulsion is unstable at a temperature of 15 °C and when the emulsion is in contact with and diluted by a factor of 10 by raw sewage throughout the range of pH 4.5 to pH 10.0.

1A.2.5 Solvents and other organic liquids

There shall be no free layer (whether floating or settled) of solvents or organic liquids.

1A.2.6 Emulsions of paint, latex, adhesive, rubber, plastic

- (a) Where such emulsions are not treatable these may be discharged into the public sewer subject to the total suspended solids not exceeding 1000 g/m³ or the concentration agreed with the Council.
- (b) The Council may determine that the need exists for pre-treatment of such emulsions if they consider that trade waste containing emulsions unreasonably interferes with the operation of the Council treatment plant e.g. reduces % UVT (ultra violet transmission).
- (c) Such emulsions of both treatable and non-treatable types, shall be discharged to the public sewer only at a concentration and pH range that prevents coagulation and blockage at the mixing zone in the public sewer.

1A.2.7 Radioactivity

Radioactivity levels shall not exceed National Radiation Laboratory Guidelines.

1A.2.8 Colour

No waste shall have colour or colouring substance that causes the discharge to be coloured to the extent that it impairs wastewater treatment processes or compromises the treated sewage discharge consent.

1A.3 Chemical characteristics

1A.3.1 pH value

The pH shall be between 6.0 and 10.0 at all times.

1A.3.2 Organic strength

1A.3.2.1

The Biochemical Oxygen Demand (BOD₅) of any waste may require to be restricted where the capacity for receiving and treating BOD₅ is limited. A BOD₅ restriction may be related to mass limits.

BOD₅ shall not exceed 1000 g/m³. For significant industry this may be reduced to 600 g/m³.

NOTE – For biological process inhibiting compounds see schedule 3(b) for the *Guidelines for Sewerage Systems: Acceptance of trade wastes (industrial waste)*

1A.3.3 Maximum concentrations

The Maximum Concentrations permissible for the chemical characteristics of an acceptable discharge are set out in table 1A.1, table 1A.2 and table 1A.3.

Table 1A.1 – General chemical characteristics

Characteristic	Maximum concentration (g/m³)
MBAS (Methylene blue active substances)	500
Ammonia (measured as N)	
- free ammonia	50
- ammonium salts	200
Kjeldahl nitrogen	250
Total phosphorus (as P)	50
Sulphate (measured as SO ₄)	500
Sulphite (measured as SO ₂)	15
Sulphide – as H ₂ S on acidification	5
Chlorine (measured as Cl ₂)	
- free chlorine	3
- hypochlorite	30
Dissolved aluminium	100
Dissolved iron	100
Boron (as B)	25
Bromine (as Br ₂)	5
Fluoride (as F)	30
Cyanide – weak acid dissociable (as CN)	1

Table 1A.2 – Heavy metals

(Mass limits may be imposed, refer to 4.2)

Metal	Maximum concentration (g/m³)
Antimony	10
Arsenic	5
Barium	10
Beryllium	0.005
Cadmium	0.5
Chromium	5
Cobalt	10
Copper	10
Lead	5)

Metal	Maximum concentration (g/m³)
Manganese	20
Mercury	0.05
Molybdenum	10
Nickel	10
Selenium	10
Silver	2
Thallium	10
Tin	20
Zinc	10

Table 1A.3 – Organic compounds and pesticides

(Mass limits may be imposed, refer to 4.2)

Compound	Maximum concentration (g/m³)
Formaldehyde (as HCHO)	50
Phenolic compounds (as phenois) excluding chlorinated phenois	50
Chlorinated phenois	0.02
Petroleum hydrocarbons	30
Halogenated aliphatic compounds	1
Monocyclic aromatic hydrocarbons	5
Polycyclic (or polynuclear) aromatic hydrocarbons (PAHs)	0.05
Halogenated aromatic hydrocarbons (HAHs)	0.002
Polychlorinated biphenyls (PCBs)	0.002
Polybrominated biphenyls (PBBs)	0.002 each
Pesticides (general) (includes insecticides, herbicides, fungicides and excludes organophosphate, organochlorine and any pesticides not registered for use in New Zealand)	0.2 in total
Organophosphate pesticides	0.1
Any organochlorine pesticides;	0.01

SCHEDULE 1B OF PART 4 – TRADE WASTE AND WASTE WATER

PROHIBITED CHARACTERISTICS

1B.1 Introduction

This schedule defines prohibited trade wastes.

1B.2 Prohibited characteristics

1B.2.1

Any discharge has prohibited characteristics if it has any solid liquid or gaseous matters or any combination or mixture of such matters which by themselves or in combination with any other matters will immediately or in the course of time:

- (a) Interfere with the free flow of sewage in the sewerage system;
- (b) Damage any part of the sewerage system;
- (c) In any way, directly or indirectly, cause the quality of the treated sewage or residual biosolids and other solids from any sewage treatment plant in the catchment to which the waste was discharged to breach the conditions of a consent issued under the Resource Management Act, or water right, permit or other governing legislation;
- (d) Prejudice the occupational health and safety risks faced by sewerage workers;
- (e) After treatment be toxic to fish, animals or plant life in the receiving waters;
- (f) Cause malodorous gases or substances to form which are of a nature or sufficient quantity to create a nuisance; or
- (g) Have a colour or colouring substance that causes the discharge from any Sewage treatment plant to receiving waters to be coloured.

1B.2.2

A discharge has prohibited characteristics if it has any characteristic which exceeds the concentration or other limits specified in Schedule 1A unless specifically approved for that particular consent.

1B.2.3

A discharge has a prohibited characteristic if it has any amount of:

- (a) Harmful solids, including dry solid wastes and materials which combine with water to form a cemented mass;
- (b) Liquid, solid or gas which could be flammable or explosive in the wastes, including oil, fuel, solvents (except as allowed for in Schedule 1A), calcium carbide, and any other material which is capable of giving rise to fire or explosion hazards either spontaneously or in combination with sewage;
- (c) Asbestos;

(d) The following organo-metal compounds:

Tin (as tributyl and other organotin compounds);

(e) Genetic wastes, as follows:

All wastes that contain or are likely to contain material from a genetically modified organism that is not in accordance with an approval under the Hazardous Substances and New Organisms Act. The material concerned may be from premises where the genetic modification of any organism is conducted or where a genetically modified organism is processed;

(f) Any health care waste prohibited for discharge to a sewerage system by NZS 4304 or any pathological or histological wastes; or

(g) Radioactivity levels in excess of the National Radiation Laboratory Guidelines.

1B.2.4

Any condensing water or stormwater which can practically be removed, or any trade wastes to which either condensing water or stormwater has been added.

SCHEDULE 1C OF PART 4 – TRADE WASTE AND WASTE WATER

SYSTEM OF CHARGING IN RESPECT OF VOLUME AND STRENGTH OF TRADE WASTES AND SPECIAL WASTES

1C.1 Charging system

The charging methods involve assessing the full life costs of the sewerage infrastructure, treatment plant, the disposal systems and costs associated with the administration, management and monitoring of trade wastes. Charges are then allocated from either a uniform annual charge or unit costs for volume and the various pollutants that are removed. The total treatment costs are built up by allocating costs to the reticulation network, individual treatment process units, the disposal system, administration and management. All charges will be reviewed annually as part of the LTCCP and/or Annual Plan Process

Note: Please check for the latest years charges.

1C.2 Charging categories

There are three charging categories, which are based on a customer's sewage contribution to the sewerage system

1C.2.1 *Annual Trade Waste Consent Fee*

All trade waste customers will pay an annual trade waste consent fee in relation to their discharge. The consent fee will be reviewed on an annual basis as part of the Council's LTCCP and/or Annual Plan Process.

1C.2.2 *Volume Only Based Charges*

This charging mechanism will apply to small industrial / commercial trade waste customers. Charges will be based on metered water use and calculated in proportion to the normal domestic discharge.

1C.2.3 *Tankered Waste Charges*

Tankered waste dischargers may be charged using either a Fixed Tankered Waste Charge or Flow and Load Based Charge. It is at the discretion of the Council to which charge applies.

- (a) The Flow and Load Based Charge will be calculated using the formula in schedule 1C.3.
- (b) The Fixed Tankered Waste Charge shall be calculated using a set fee per cubic metre.

1C.2.4 Flow and Load Based Charges with Council Monitoring

This charging mechanism will apply to trade waste customers who have a significant pollutant load discharging into the Sewerage System. Results of monitoring will be used to determine Trade Waste charges on a flow and pollutant load basis. Self-monitoring may be acceptable for some Trade Waste discharges.

1C.3 Charging Formula

The flow and load charges are derived from the following general charging formula.

$$(V \times Vop) + (Fc \times Fcap) + (SS \times SSop) + (SSc \times SScap) + (COD \times CODop) + (CODc \times CODcap) + (TKN \times TKNop) + (TKNc \times TKNcap) + (X \times Xop) + (Xc \times Xcap)$$

Table of Parameters with descriptions:

V	The average Volume discharged
Vop	The Volume operational unit rate \$ /m ³
SS	The average mass of Suspended Solids (SS) discharged
SSop	The SS operational unit rate \$ / kg
COD	The average mass of Chemical Oxygen Demand (COD) discharged
CODop	The COD operational unit rate \$ / kg
TKN	The average mass of Total Kjeldahl Nitrogen (TKN) discharged.
TKNop	The TKN operational unit rate \$ / kg
X	The mass of substance X
Xop	The Substance X operational unit rate \$ / kg
Vc	The total consented Volume load
Vcap	The Volume capital unit rate \$ /m ³
SSc	The total consented Suspended Solids (SS) load
SScap	The SS capital unit rate \$ / kg
CODc	The total consented Chemical Oxygen Demand (COD) load
CODcap	The COD capital unit rate \$ / kg
TKNc	The total consented Total Kjeldahl Nitrogen (TKN) load.
TKNcap	The TKN capital unit rate \$ / kg
Xc	The total consented substance X load
Xcap	The Substance X capital unit rate \$ / kg

Note: The Council may substitute COD with Biological Oxygen Demand (BOD).

On investigation of a specific trade waste characteristic, substance X can be identified and an additional rate shall be negotiated with the customer.

The unit rates for each parameter of the above formula are based on the operating and capital expenditure for the previous January – December period and remain constant throughout the following financial year.

SCHEDULE 1D OF PART 4 – TRADE WASTE AND WASTE WATER

TRADE WASTE CHARGE CATEGORIES

Fees and charges are set by the Council pursuant to Section 150 of the Local Government Act 2002. This may be done by the annual planning process, fee setting or a similar transparent public process in accordance with the Local Government Act, 2002.

In the following table the Council states what categories it will charge, or may charge, under the tenure of clause 2 of Part 4 (Waste and Water) of the Hauraki District Bylaw, 2007.

Category	Description
A1 Connection fee	Payable on application for connection to discharge
A2 Compliance monitoring	The cost of sampling and analysis of trade waste discharges
A3 Disconnection fee	Payable following a request for disconnection from sewerage system
A4 Trade Waste application fee	Payable on an application for a trade waste discharge
A5 Re-inspection fee	Payable for each re-inspection visit by the Council where a notice served under clause 2 of Part 4 (Waste and Water) of the Hauraki District Bylaw, 2007 has not been complied with by the trade waste discharger
A6 Special costs for loan charges	Additional costs for servicing loans raised for the purposes of constructing or improving the sewerage system
A7 Temporary Discharge fee	Payable prior to receipt of Temporary Discharge
A8 Annual trade waste charges	An annual management fee for a trade waste discharge to cover the Council's costs associated with for example: <ul style="list-style-type: none"> (a) Administration; (b) General compliance monitoring; (c) General inspection of trade waste Premises; (d) Use of the Sewerage System. This charge may vary depending on the trade waste sector and category of the discharger.
A9 Rebates for Trade Premises within the District	Reduction in fees is provided for in s. 150(2). Section 150(4) of the Local Government Act, 2002 states that the fees prescribed by the Council shall not provide for the Council to recover more than the reasonable cost incurred by the Council for the matter for which the fee is charged.
A10 New or Additional Trade Premises	In no event shall the resultant charge be less than the Council's sewerage charge for the equivalent period. Pay the annual fees and a <i>pro rata</i> proportion of the various trade waste charges relative to flows and loads.

Category

B1 Waste in a Tanker

B2 Toxicity

Description

Set as a fee(s) per tanker load, or as a fee(s) per cubic metre, dependent on trade waste category

Payment based on the defined form(s) of the toxic substance(s) \$/kg and/or \$/m³